

PRIME

PRIME 3" SUPER SHALLOW LED ARCHITECTURAL SQUARE FLANGELESS DOWNLIGHT

JOB INFORMATION	TYPE:
	CATALOG NO.
	PROJECT NAME:
	COMMENTS:
PREPARED BY:	

USE OF PRODUCT

The 3" PRIME Downlight is a small aperture fixture with shallow height that may be used in residential and commercial applications. Available with die cast or spun aluminum trims, with an assortment of color temperatures, optics and dimmable drivers.

PRIME FEATURES

Color Temperature: 2700K, 3000K, 3500K, or 4000K
 SDCM: 2 step binning
 Color Rendering Index: 93+ CRI
 Optical Lens: 12°, 22°, 27°, 35°, 45°
 Trim: Die cast or spun aluminum
 LED Life: 50,000 Hours
 LED Type: Cree LED
 Driver Info: 120-277V, 50/60 Hz, PF>0.9, THD<0.20
 Warranty: 5 year limited warranty

LED ENGINE

LED engine available with CREE LEDs in 2700K, 3000K, 3500K, or 4000K in standard 93+ CRI. 2 Step MacAdam ellipse allows for color consistency between fixtures. LED mounted to aluminum heat sink for maximum life output and thermal management. LED engine is accessible from below ceiling.

FRAME CONSTRUCTION

IC rated housing constructed from 16 gauge heavy duty powder coated cold rolled steel frame. Junction box with 1/2" knockouts. Installation must be kept 3" away. Butterfly bracket included to accommodate adjustable bar hangers or C-channel (ordered separately).

ADJUSTMENT

- Housing provides for 359° locking rotation
 - Aperture collar adjusts 15°± horizontally within frame for square ceiling alignment
 - Collar notch allows for easy alignment for square applications.
 - Aperture collar compatible up to 1-1/2" ceiling thickness.
 - Accommodation for 2" or 3" ceiling thickness available upon request.

OPTICAL LENS & FILTERS (Field Replaceable)

Field replaceable optical lens available in 12°, 22°, 27°, 35° and 45°. Easily achieve narrow spot to wide flood beam pattern. Accepts up to 2 filters.

DIMMING

Available in 2 driver selections. **(ID)** Standard all-inclusive ELV(120V), Triac(120V), and 0-10V(120-277V) dimming driver called Intelligent Drive, 120-277V. **(PEQ0)** Lutron Hi-Lume Premier Ecosystem 0.1% w/soft on, fade to black dimming, 120-277V.

THERMAL MANAGEMENT

Ambient temperatures at fixture location should not exceed -20° to 40°C.

TRIM

Trim available in die cast or spun aluminum. Consult factory for made to order finishes. Flanged trim is compatible with all ceiling materials.

EMERGENCY BATTERY

Optional emergency battery available for a minimum of 90 minutes with Remote test switch in 800 delivered lumens.

LABELS/COMPLIANCE/WARRANTY

- CSA Listed for US and Canada
 - Dry/Damp/Wet location rated.
 - Energy Star
 - Title 24, JA8 Compliant
 - 5 Year limited warranty



ORDERING INFO

RPA3S						
Series	Lumens	Color Temp	Voltage	Dimming	Optical Lens	Filter
PRIME	8 - 825 lm	27 - 2700K	UNV - 120-277V	ID ¹ - Standard all-inclusive ELV, Triac, and 0-10V dimming driver (Intelligent Drive)	12 - 12°	None - Leave blank
SERIES	12 - 1235 lm	30 - 3000K	120 - 120V	PEQ0 - Lutron Hi-lume Premier Ecosystem 0.1% w/soft on, fade to black dimming	22 - 22°	F - Frosted
	15 - 1500 lm	35 - 3500K	347 - 347V		27 - 27°	H - Honeycomb
		40 - 4000K			35 - 35°	S - Solite filter
					45 - 45°	L - Linear filter

Housing Type	Aperture	Frame Accessories	Collar	Option
IC - IC Super Shallow New Construction	SLDP - Square Flangeless Downlight Plaster SLDM - Square Flangeless Downlight Millwork	AH - Adjustable bar hanger C - C Channel bar hanger B - Flat bar hanger	Blank - 1.5" Depth 20 - 2" Depth 30 - 3" Depth MTO - Made to order	ERB ³ - Emergency battery with remote switch (800 Lumens) CP - Chicago Plenum

TRIM ORDERING INFORMATION

Aperture Size / Shape / Trim Type / Style	Bevel Opening	Bevel Finish	Options
3SLO - 3" Square Flangeless Open	Die Cast CL - Die cast large opening CS - Die cast small opening	W - White H - Haze B - Black BZ - Bronze C - Clear MTO - Made to order	WL - Wet location



1. Standard driver.
 2. Ceiling access required.
 3. Must specify logarithmic or linear eldoLED driver.

PRIME

PRIME 3" SUPER SHALLOW LED ARCHITECTURAL SQUARE FLANGELESS DOWNLIGHT

DIMENSIONS


IC Housing



Heatsink




LED Holder (Body)




Optics




Filter



LED Holder (Head)




Trim




FRAME ACCESSORIES

B



Flat Bar Hanger




C




C Channel Bar Hanger




AH



C Channel Bar Hanger



COLLAR DEPTH PER CEILING THICKNESS



PRIME

PRIME 3" SUPER SHALLOW LED ARCHITECTURAL SQUARE FLANGELESS DOWNLIGHT


AT-A-GLANCE TECHNICAL INFORMATION

3" PRIME DOWNLIGHT

RPA - 8L

12° Beam, Square Large Open

TEST DATE	2019-07-12
SERIES	RPA3-8L-30K-12°- Square Large Open
LUMENS	786.4 LM
WATTS	10 W
CCT	3000K




Zone	Lumens	%Lamp	%Luminaire
0-30	699.2	88.9%	88.8%
0-40	741.2	94.3%	94.1%
0-60	780.8	99.3%	99.1%
60-90	7.0	0.9%	0.9%
0-90	787.8	100.2%	100%

RPA - 8L

22° Beam, Square Large Open

TEST DATE	2019-07-12
SERIES	RPA3-8L-30K-22°- Square Large Open
LUMENS	794 LM
WATTS	10 W
CCT	3000K




Zone	Lumens	%Lamp	%Luminaire
0-30	691.7	87.1%	87%
0-40	749.6	94.4%	94.3%
0-60	788.3	99.3%	99.2%
60-90	6.6	0.8%	0.8%
0-90	794.9	100.1%	100%

RPA - 8L

27° Beam, Square Large Open

TEST DATE	2019-07-12
SERIES	RPA3-8L-30K-27°- Square Large Open
LUMENS	816.2 LM
WATTS	10 W
CCT	3000K




Zone	Lumens	%Lamp	%Luminaire
0-30	775.4	89.9%	89.9%
0-40	828.3	96.1%	96%
0-60	858.2	99.5%	99.5%
60-90	4.7	0.5%	0.5%
0-90	862.9	100.1%	100%

RPA - 8L

35° Beam, Square Large Open

TEST DATE	2019-07-12
SERIES	RPA3-8L-30K-35°- Square Large Open
LUMENS	827.2 LM
WATTS	10 W
CCT	3000K




Zone	Lumens	%Lamp	%Luminaire
0-30	706.6	85.4%	85.5%
0-40	779.8	94.3%	94.3%
0-60	821.5	99.3%	99.4%
60-90	5.3	0.6%	0.6%
0-90	826.8	100%	100%

RPA - 8L

45° Beam, Square Large Open

TEST DATE	2019-07-12
SERIES	RPA3-8L-30K-45°- Square Large Open
LUMENS	800.8 LM
WATTS	10 W
CCT	3000K



Zone	Lumens	%Lamp	%Luminaire
0-30	565.0	70.6%	70.6%
0-40	709.2	88.6%	88.6%
0-60	793.7	99.1%	99.2%
60-90	6.7	0.8%	0.8%
0-90	800.5	100%	100%

PRIME


PRIME 3" SUPER SHALLOW LED ARCHITECTURAL SQUARE FLANGELESS DOWNLIGHT

AT-A-GLANCE TECHNICAL INFORMATION

3" PRIME DOWNLIGHT

RPA - 15L 12° Beam, Square Large Open

TEST DATE 2019-07-12
 SERIES RPA3-15L-30K-12°- Square Large Open
 LUMENS 1410 LM
 WATTS 20 W
 CCT 3000K




Zone	Lumens	%Lamp	%Luminaire
0-30	1,253.1	88.9%	88.7%
0-40	1,327.7	94.2%	94%
0-60	1,398.8	99.2%	99.1%
60-90	13.3	0.9%	0.9%
0-90	1,412.2	100.2%	100%

Zone Lumen Summary

RPA - 15L 22° Beam, Square Large Open

TEST DATE 2019-07-12
 SERIES RPA3-15L-30K-22°- Square Large Open
 LUMENS 1422 LM
 WATTS 20 W
 CCT 3000K




Zone	Lumens	%Lamp	%Luminaire
0-30	1,235.7	86.9%	86.8%
0-40	1,340.5	94.3%	94.2%
0-60	1,410.9	99.2%	99.1%
60-90	12.7	0.9%	0.9%
0-90	1,423.6	100.1%	100%

Zone Lumen Summary

RPA - 15L 27° Beam, Square Large Open

TEST DATE 2019-07-12
 SERIES RPA3-15L-30K-27°- Square Large Open
 LUMENS 1462.7 LM
 WATTS 20 W
 CCT 3000K




Zone	Lumens	%Lamp	%Luminaire
0-30	1,263.5	86.4%	86.4%
0-40	1,377.9	94.2%	94.2%
0-60	1,450.7	99.2%	99.2%
60-90	12.0	0.8%	0.8%
0-90	1,462.7	100%	100%

Zone Lumen Summary

RPA - 15L 35° Beam, Square Large Open

TEST DATE 2019-07-12
 SERIES RPA3-15L-30K-35°- Square Large Open
 LUMENS 1495 LM
 WATTS 20 W
 CCT 3000K




Zone	Lumens	%Lamp	%Luminaire
0-30	1,278.6	85.5%	85.5%
0-40	1,409.4	94.3%	94.3%
0-60	1,484.4	99.3%	99.3%
60-90	10.5	0.7%	0.7%
0-90	1,494.9	100%	100%

Zone Lumen Summary

RPA - 15L 45° Beam, Square Large Open

TEST DATE 2019-07-12
 SERIES RPA3-15L-30K-45°- Square Large Open
 LUMENS 1457.1 LM
 WATTS 20 W
 CCT 3000K



Zone	Lumens	%Lamp	%Luminaire
0-30	1,025.8	70.4%	70.4%
0-40	1,288.3	88.4%	88.4%
0-60	1,443.3	99%	99.1%
60-90	13.2	0.9%	0.9%
0-90	1,456.5	100%	100%

Zone Lumen Summary

PRIME


PRIME 3" SUPER SHALLOW LED ARCHITECTURAL SQUARE FLANGELESS DOWNLIGHT

AT-A-GLANCE TECHNICAL INFORMATION

3" PRIME DOWNLIGHT

RPA - 12L 12° Beam, Square Small Open

TEST DATE	2019-07-12
SERIES	RPA3-12L-30K-12°- Square Small Open
LUMENS	1169.4 LM
WATTS	14 W
CCT	3000K




Zone	Lumens	%Lamp	%Luminaire
0-30	1,033.9	88.4%	88.3%
0-40	1,095.9	93.7%	93.6%
0-60	1,157.1	98.9%	98.8%
60-90	14.2	1.2%	1.2%
0-90	1,171.3	100.2%	100%

Zone Lumen Summary

RPA - 12L 22° Beam, Square Small Open

TEST DATE	2019-07-12
SERIES	RPA3-12L-30K-22°- Square Small Open
LUMENS	1176.9 LM
WATTS	14 W
CCT	3000K




Zone	Lumens	%Lamp	%Luminaire
0-30	1,019.7	86.6%	86.5%
0-40	1,104.4	93.8%	93.7%
0-60	1,164.4	98.9%	98.8%
60-90	13.9	1.2%	1.2%
0-90	1,178.3	100.1%	100%

Zone Lumen Summary

RPA - 12L 27° Beam, Square Small Open

TEST DATE	2019-07-12
SERIES	RPA3-12L-30K-27°- Square Small Open
LUMENS	1213.9 LM
WATTS	14 W
CCT	3000K




Zone	Lumens	%Lamp	%Luminaire
0-30	1,053.2	86.8%	86.7%
0-40	1,142.7	94.1%	94.1%
0-60	1,202.1	99%	99%
60-90	12.5	1%	1%
0-90	1,214.6	100.1%	100%

Zone Lumen Summary

RPA - 12L 35° Beam, Square Small Open

TEST DATE	2019-07-12
SERIES	RPA3-12L-30K-35°- Square Small Open
LUMENS	1237.7 LM
WATTS	14 W
CCT	3000K




Zone	Lumens	%Lamp	%Luminaire
0-30	1,056.7	85.4%	85.4%
0-40	1,163.9	94%	94%
0-60	1,227.2	99.1%	99.1%
60-90	10.7	0.9%	0.9%
0-90	1,237.9	100%	100%

Zone Lumen Summary

RPA - 12L 45° Beam, Square Small Open

TEST DATE	2019-07-12
SERIES	RPA3-12L-30K-45°- Square Small Open
LUMENS	1213 LM
WATTS	14 W
CCT	3000K



Zone	Lumens	%Lamp	%Luminaire
0-30	858.7	70.8%	70.8%
0-40	1,075.3	88.7%	88.7%
0-60	1,200.4	99%	99%
60-90	12.4	1%	1%
0-90	1,212.8	100%	100%

Zone Lumen Summary

PRIME


PRIME 3" SUPER SHALLOW LED ARCHITECTURAL SQUARE FLANGELESS DOWNLIGHT

AT-A-GLANCE TECHNICAL INFORMATION

3" PRIME DOWNLIGHT

RPA - 15L 12° Beam, Square Small Open

TEST DATE	2019-07-12
SERIES	RPA3-15L-30K-12°- Square Small Open
LUMENS	1435.9 LM
WATTS	20 W
CCT	3000K




Zone	Lumens	%Lamp	%Luminaire
0-30	1,276.6	88.9%	88.7%
0-40	1,351.5	94.1%	93.9%
0-60	1,424.3	99.2%	99%
60-90	14.2	1%	1%
0-90	1,438.5	100.2%	100%

Zone Lumen Summary

RPA - 15L 22° Beam, Square Small Open

TEST DATE	2019-07-12
SERIES	RPA3-15L-30K-22°- Square Small Open
LUMENS	1463.8 LM
WATTS	20 W
CCT	3000K




Zone	Lumens	%Lamp	%Luminaire
0-30	1,272.9	87%	86.9%
0-40	1,376.9	94.1%	94%
0-60	1,451.0	99.1%	99%
60-90	14.5	1%	1%
0-90	1,465.5	100.1%	100%

Zone Lumen Summary

RPA - 15L 27° Beam, Square Small Open

TEST DATE	2019-07-12
SERIES	RPA3-15L-30K-27°- Square Small Open
LUMENS	1491.3 LM
WATTS	20 W
CCT	3000K




Zone	Lumens	%Lamp	%Luminaire
0-30	1,300.8	87.2%	87.2%
0-40	1,408.5	94.4%	94.4%
0-60	1,479.7	99.2%	99.2%
60-90	12.7	0.8%	0.8%
0-90	1,492.3	100.1%	100%

Zone Lumen Summary

RPA - 15L 35° Beam, Square Small Open

TEST DATE	2019-07-12
SERIES	RPA3-15L-30K-35°- Square Small Open
LUMENS	1506.2 LM
WATTS	20 W
CCT	3000K




Zone	Lumens	%Lamp	%Luminaire
0-30	1,290.4	85.7%	85.7%
0-40	1,420.0	94.3%	94.3%
0-60	1,495.1	99.3%	99.3%
60-90	11.0	0.7%	0.7%
0-90	1,506.1	100%	100%

Zone Lumen Summary

RPA - 15L 45° Beam, Square Small Open

TEST DATE	2019-07-12
SERIES	RPA3-15L-30K-45°- Square Small Open
LUMENS	1461.3 LM
WATTS	20 W
CCT	3000K



Zone	Lumens	%Lamp	%Luminaire
0-30	1,036.8	70.9%	71%
0-40	1,297.5	88.8%	88.8%
0-60	1,448.0	99.1%	99.1%
60-90	13.2	0.9%	0.9%
0-90	1,461.2	100%	100%

Zone Lumen Summary