


PROJECT: _____


MODEL #: _____

LOCATION: _____

CONTACT: _____



MOUNTING FEATURES



USE OF PRODUCT

The Architectural Square Luminaire Pull Down Series may be used in hospitality, commercial, retail, and residential applications. This product will reduce energy consumption, emits little heat, and reduces cooling loads for added costs savings. Approximately 75% in energy savings compared to incandescent light source.

HOUSING

Rugged aluminum housing.

ARCHITECTURAL SQUARE LUMINAIRE FEATURES

- Wattage: 12 Watts
- Lumens: 830 Lumens
- Voltage: 120V
- Color Temperature: 2700K, 3000K, 3500K, or 4000K
- R9 Value: 85
- Color Rendering Index: 93 CRI Typical
- LED Life: 50,000 hours
- LED type: Cree LED for maximum light output
- Versatility: Interchangeable optics available in 19° and 38°. 365° horizontal rotations; 65° vertical drop from nadir.
- Warranty: 5 Year Limited Warranty

LED Driver

Durable 120 Volt dimmable driver provides high power factor with optimum thermal management to prevent damage caused by high temperature.

Dimming

The Architectural Square Luminaire Pull Down Series is dimmable to 15% with standard 120 Volt electronic low voltage dimmers, various incandescent/magnetic low voltage dimmers, or to 5% with select dimmers.

Mounting

The Architectural Square Luminaire Pull Down Series may be cable hung, stem mount, surface mount or wall mounted.

Module Mechanics

- The Architectural Square Luminaire Pull Down Series provides 359° horizontal rotation within module and 65° vertical drop from nadir.
- Carefully designed heat sink keeps junction temperatures below unsuitable levels by keeping heat away from the LEDs.
- Diffused lens allows for even light output, glare control, and conceals LED from view.

Labels / Compliance

CSA Classified
CSA Classified for damp locations.

ORDERING INFO

RFL	4E	SL				
-----	----	----	--	--	--	--

Series	Diameter	Shape	Length	Watts/Lumens	Color Temp.	Luminaire Finish
RFL	4E - 5-1/8"	SL - Square Luminaire	12 - 12" MTO - Made to order	8L - 12Watts/830 Lumens (120V)	27 - 2700K 30 - 3000K 35 - 3500K 40 - 4000K	BL - Black W - White SL - Silver MTO - Made to order

				1 18" standard length, consult factory for other 2 5ft standard cable length
--	--	--	--	---

Pull Down Finish	Beam Angle	Configuration	Mounting
W - White BL - Black SN - Satin Nickel BZ - Bronze	19 - 19° 38 - 38°	DL - Down Light	PH ¹ - Pendant Hung SC ² - Single Cable TC - Triple Cable QC - Quadeuple Cable SM - Surface Mount WM - Wall Mount