



T616LED-E

LED EYELID ROUND WALL PACK

JOB INFORMATION

Type: _____
 Catalog No: _____
 Project Name: _____
 Comments: _____

 Prepared by: _____

T616LED-E

FEATURES

USE OF PRODUCT

The intended use of this product is for decorative wall mount, building accents, pedestrian walkways, public access areas, or to accent landscape areas.

HOUSING

Die Cast gasketed aluminum housing with integral heat sinking and driver compartment. Nickel-Plated Stainless Steel Hardware.

FINISH

Matt-finished, architectural bronze powdercoat over a precise chromate conversion coating. Available in standard dark polyester bronze or consult factory for made to order architectural finishes.

OPTICS

Polycarbonate Opal Lens is sealed by a one-piece silicon gasket which prohibits entrance of outside contamination. Type IV distribution.

LED

High output LEDs offer a minimum estimated operating life of 50,000 hours in 3000K, 4000K, or 5000K (standard) with CRI>80.

DRIVER

Durable and long lasting LED driver operates at 120-277V and boasts a 90% power factor at 50 to 60 Hz with 0-10V Dimming Constant Current. Driver protections includes: Output open load, over-current and short-circuit, and over-temperature with auto recovery. -40°C Min Temp. 50°C Max Temp.

MOUNTING

Surface mount.

LISTINGS/COMPLIANCE

- CEC Compliant emergency driver
- CSA -Suitable for wet location.
- ANSI/UL 1598
- 8750 IP65 Sealed LED compartment.



ORDERING INFO

SERIES	WATTAGE	COLOR TEMPERATURE	VOLTAGE	FINISH	OPTIONS
T616LED-E	12W - 12W	30K - 3000K	UNV - 120V-277V	BZ ¹ - Bronze	PC - Photocell 120-277V
	17W - 17W	40K - 4000K		MTO ² - Made to order	S2 - Microwave Sensor w/Dimming
	25W - 25W	50K - 5000K		MGTO ² - Marine grade made to order	SP10 - Surge protection 10KV
					EM - Emergency battery
					CEM - Cold pack emergency battery (Integral)

Notes
 1. Standard finish.
 2. RAL number required.



T616LED-E

LED EYELID ROUND WALL PACK

DIMENSIONS

