




T736LED

15" CONICAL LED
CANOPY LUMINAIRE

JOB INFORMATION	TYPE:
	CATALOG NO.
	PROJECT NAME:
	COMMENTS:
PREPARED BY:	

DIMENSIONS



FEATURES



USE OF PRODUCT

The intended use of this product is in parking areas, entrances, walkways, underpasses, loading docks, or recreation areas.

HOUSING

Rugged round die cast aluminum housing. Coin plugs with O-rings for conduit and photocell on sides and back.

FINISH

Matt-finished, architectural white powdercoat over a precise chromate conversion coating. Consult factory for made to order architectural finishes.

OPTICS

Anodized aluminum with white powdercoat steel reflector. Extended clear prismatic polycarbonate lens with stainless steel screw. Lens is sealed by one-piece silicon gasket prohibits entrance of outside contaminants.

LED

High output LEDs offer a minimum estimated operating life of 50,000 hours in 3000K, 3500K, 4000K, or 5000K with CRI>83. LEDs placed on high performance aluminum heatsink for reduced junction temperatures and extended life.

DRIVER

Durable and long lasting LED driver operates at 120-277V and boasts a 90% power factor at 50 to 60 Hz with 0-10V Dimming Constant Current. Driver protections includes: Output open load, over-current and short-circuit, and over-temperature with auto recovery. -30°C Min Temp. 40°C Max Temp. Step down transformer may be utilized for 480V or 347V applications.

MOUNTING

Built-in template for mounting to electrical box or use 1/2" surface conduit.

LISTINGS/COMPLIANCE

- CEC Compliant emergency drive
- CSA - Suitable for wet locations

ACCESSORIES: Wire guard available upon request.

ORDERING INFO

T736LED						
Series	Watt/lumens	Voltage	Color temperature	Mounting	Finish	Options
T-SERIES LED	10 - 10W/1050 lm	UNV -120V-277V 347¹ - 347V 480¹ - 480V	30 - 3000K	S - Surface P² - Pendant	BZ - Bronze MTO³ - Made to order MGTO³ - Marine Grade made to order	PC1 - Photocell 120V PC2 - Photocell 277V MS - Motion sensor (Bi-Level) EM - Emergency battery SP10 - Surge protection 10KV
	18 - 18W/1890 lm		35 - 3500K			
	30 - 30W/3150 lm		40 - 4000K			
	45 - 45W/4725 lm		50 - 5000K			
57 - 57W/5985 lm						

Wireless Control

- LPH** - Limelight by Lutron Integral module with PIR sensor and external antennae, - High mounting height
- LPM** - Limelight by Lutron Integral module with PIR sensor and external antennae - Medium mounting height
- LPL** - Limelight by Lutron Integral module with PIR sensor and external antennae - Low mounting height
- LRF** - Limelight by Lutron Integral module with external antennae, RF Only

Notes:

1. Step down transformer included
2. Standard 18" length; consult factory for other.
3. RAL number required.