



RCYA3

3" LED ARCHITECTURAL CYLINDER

JOB INFORMATION

Type: _____
Catalog No: _____
Project Name: _____
Comments: _____
Prepared by: _____

RCYA3

USE OF PRODUCT

The RCYA Series may be used in hospitality, commercial, retail, and residential interior applications. This series is available in two sizes (RCYA6 & RCYA3) and is wattage selectable, color temperature selectable, and beam angle selectable. Optional filters available upon request. Multiple mounting options: Surface mount, adjustable surface mount, cord mount, pendant mount.

RCYA3 FEATURES

- Wattage selectable: 13W, 19W, 25W
- Color temperature selectable: 2700K, 3000K, 3500K, 4000K, 5000K
- Beam angle selectable: 18° to 50°
- Knife edge appearance
- Made to order finish available upon request

HOUSING

Rugged aluminum housing to effectively and passively remove heat from LED.

LED ENGINE

Color temperature selectable with 90 CRI LEDs

DRIVER

- 0-10V (120V-277V) dimming driver with range of 1% - 100%.
- Driver power factor >0.9, THD <20%
- Operating Temperature Range: -20°C - 40°C (-4°F - 104°F)

EMERGENCY BATTERY

Utilize remote 8W emergency battery with remote test switch. Ceiling access is required to replace the em unit

BEAM ANGLE & FILTERS

Beam angle is continuously adjustable from 18° to 50° degrees with preset stops at 18°, 24°, 36°, and 50°. Optional linear lens, honeycomb louver, and soft optics available upon request. (Lumens decrease)

MOUNTING

Surface mount, adjustable surface mount (for wall or ceiling), cord mount, and pendant mount.

LABELS/COMPLIANCE/WARRANTY

- UL certified
- 5-year limited warranty.



ORDERING INFORMATION

Series	Wattage	Voltage	Color Temperature	Beam Angle	Filter
RCYA3	WS25 - Wattage Selectable (13W, 19W, 25W) L13W - Locked at 13W L19W - Locked at 19W L25W - Locked at 25W	UNV - 120-277V	5CTS - (2700K, 3000K, 3500K, 4000K, 5000K) L27K - Locked at 2700K L30K - Locked at 3000K L35K - Locked at 3500K L40K - Locked at 4000K L50K - Locked at 5000K	BA1850 - 18° - 50° Adjustable	None - Included L - Linear H - Honey Comb S - Softening Lens

Reflector Finish	Cylinder Finish	Mounting	Options
W - White B - Black MTO - Made to Order	W - White B - Black MTO - Made to Order	Stem PH3SC1W ¹ - 1 ft White Stem Pendant with Shallow Canopy PH3SC1B ¹ - 1 ft Black Stem Pendant with Shallow Canopy PH3SC2W ¹ - 2 ft White Stem Pendant with Shallow Canopy PH3SC2B ¹ - 2 ft Black Stem Pendant with Shallow Canopy PH3DC1W ¹ - 1 ft White Stem Pendant with Deep Canopy PH3DC1B ¹ - 1 ft Black Stem Pendant with Deep Canopy PH3DC2W ¹ - 2 ft White Stem Pendant with Deep Canopy PH3DC2B ¹ - 2 ft Black Stem Pendant with Deep Canopy Adjustable Stem PH3SC1WADJ ¹ - 1 ft White Stem Pendant, Adjustable Fixture, Shallow Canopy PH3SC1BADJ ¹ - 1 ft Black Stem Pendant, Adjustable Fixture, Shallow Canopy PH3SC2WADJ ¹ - 2 ft White Stem Pendant, Adjustable Fixture, Shallow Canopy PH3SC2BADJ ¹ - 2 ft Black Stem Pendant, Adjustable Fixture, Shallow Canopy PH3DC1WADJ ¹ - 1 ft White Stem Pendant, Adjustable Fixture, Deep Canopy PH3DC1BADJ ¹ - 1 ft Black Stem Pendant, Adjustable Fixture, Deep Canopy PH3DC2WADJ ¹ - 2 ft White Stem Pendant, Adjustable Fixture, Deep Canopy PH3DC2BADJ ¹ - 2 ft Black Stem Pendant, Adjustable Fixture, Deep Canopy Cord CP3SW ² - White Cord Pendant with Shallow Canopy CP3SB ² - Black Cord Pendant with Shallow Canopy CP3DW ² - White Cord Pendant with Deep Canopy CP3DB ² - Black Cord Pendant with Deep Canopy Surface SM3SW - White Surface Mount with Shallow Canopy SM3SB - Black Surface Mount with Shallow Canopy SM3DW - White Surface Mount with Deep Canopy SM3DB - Black Surface Mount with Deep Canopy Adjustable Surface ASCW ³ - White Adjustable Surface Mount ASCB ³ - Black Adjustable Surface Mount	SP1W ¹ - 1 ft White Stem Pendant SP1B ¹ - 1 ft Black Stem Pendant SP2W ¹ - 2 ft White Stem Pendant SP2B ¹ - 2 ft Black Stem Pendant ER8W - 8W Emergency Battery with Remote Test Switch Notes 1. 1ft and 2ft stems are linkable up to 12 ft. Consult factory for made to order lengths. 2. 5 ft is the standard cord length. Consult factory for made to order lengths. 3. Can be extended with stem pendant.



RCYA3

3" LED ARCHITECTURAL CYLINDER

PERFORMANCE CHART


Optics		18°	24°	36°	50°
13W	Delivered Lumens	1322	1375	1414	1386
19W	Delivered Lumens	1880	1934	1973	1945
25W	Delivered Lumens	2360	2462	2535	2483

* Values are listed at 3000K, 90+ CRI with a white bevel & trim.

COLOR TEMPERATURE MULTIPLIER FOR DELIVERED LUMENS

2700K	3000K	3500K	4000K	5000K
0.95	1.00	1.04	1.07	1.09


BEAM SPREAD



RCYA3


3" LED ARCHITECTURAL CYLINDER

RCYA3 DIMENSIONS





STEM PENDANT

**PH3SC1W, PH3SC1B,
PH3SC2W, PH3SC2B**
Stem Pendant with
Shallow Canopy




**PH3DC1W, PH3DC1B,
PH3DC2W, PH3DC2B**
Stem Pendant with
Deep Canopy



RCYA3


3" LED ARCHITECTURAL CYLINDER

ADJUSTABLE STEM PENDANT





PH3SC1WADJ, PH3SC1BADJ,
PH3SC2WADJ, PH3SC2BADJ

Stem Pendant with
Shallow Canopy



PH3DC1WADJ, PH3DC1BADJ,
PH3DC2WADJ, PH3DC2BADJ

Stem Pendant with
Deep Canopy



1ft and 2ft stems are linkable up to 12 ft.
Consult factory for made to order lengths.


RCYA3

3" LED ARCHITECTURAL CYLINDER

CORD PENDANT


CP3SW, CP3SB

Cord Pendant with
Shallow Canopy



CP3DW, CP3DB


Cord Pendant with
Deep Canopy



SURFACE MOUNT


SM3SW, SM3SB

Surface Mount with
Shallow Canopy



SM3DW, SM3DB



Surface Mount with
Deep Canopy





RCYA3

3" LED ARCHITECTURAL CYLINDER

ADJUSTABLE SURFACE MOUNT



DEEP CANOPY FOR SURFACE, CORD, OR PENDANT MOUNT



RCYA3

3" LED ARCHITECTURAL CYLINDER

8W EMERGENCY BATTERY

