



RCYA6

6" LED ARCHITECTURAL CYLINDER

JOB INFORMATION

Type: _____
Catalog No: _____
Project Name: _____
Comments: _____
Prepared by: _____

RCYA6

USE OF PRODUCT

The RCYA series may be used in hospitality, commercial, retail, and residential interior applications. This series is available in two sizes (RCYA6 & RCYA3) and is wattage selectable, color temperature selectable, and beam angle selectable. Optional filters available upon request. Multiple mounting options: Surface mount, adjustable surface mount, cord mount, pendant mount.

RCYA3 FEATURES

- Wattage selectable: 20W, 30W, 40W
- Color temperature selectable: 2700K, 3000K, 3500K, 4000K, 5000K
- Beam angle selectable: 18° to 50°
- Knife edge appearance
- Made to order finish available upon request

HOUSING

Rugged aluminum housing to effectively and passively remove heat from LED.

LED ENGINE

Color temperature selectable 90 CRI

DRIVER

- Triac and 0-10V (120V-277V) dimming driver with range of 1% - 100%.
- Driver power factor >0.9, THD <20%
- Operating Temperature Range: -20°C - 40°C (-4°F - 104°F)

EMERGENCY BATTERY

May utilize an 8W remote emergency battery (ceiling access required) with a remote test switch. Alternatively, may utilize a 4W integral emergency battery with an integral test switch.

BEAM ANGLE & FILTERS

Beam angle is continuously adjustable from 18° to 50° degrees with preset stops at 18°, 24°, 36°, and 50°. Optional linear lens, honeycomb louver, and soft optics available upon request. (Lumens decrease)

MOUNTING

Surface mount, adjustable surface mount (for wall or ceiling), cord mount, and pendant mount.

LABELS/COMPLIANCE/WARRANTY

- UL certified
- 5-year limited warranty.



ORDERING INFORMATION

Series	Wattage	Dimming	Color Temperature	Beam Angle	Filter
RCYA6	WS40 - Wattage Selectable (20W, 30W, 40W) L20W - Locked at 20W L30W - Locked at 30W L40W - Locked at 40W	ID - Triac (120V), and 0-10V (120-277V) Dimming Driver	5CTS - (2700K, 3000K, 3500K, 4000K, 5000K) L27K - Locked at 2700K L30K - Locked at 3000K L35K - Locked at 3500K L40K - Locked at 4000K L50K - Locked at 5000K	BA1850 - 18° - 50° Adjustable	None - Included L - Linear H - Honey Comb S - Softening Lens
Reflector Finish	Cylinder Finish	Mounting		Options	
W - White B - Black MTO - Made to Order	W - White B - Black MTO - Made to Order	Stem PH6SC1W¹ - 1 ft White Stem Pendant with Shallow Canopy PH6SC1B¹ - 1 ft Black Stem Pendant with Shallow Canopy PH6SC2W¹ - 2 ft White Stem Pendant with Shallow Canopy PH6SC2B¹ - 2 ft Black Stem Pendant with Shallow Canopy PH6DC1W¹ - 1 ft White Stem Pendant with Deep Canopy PH6DC1B¹ - 1 ft Black Stem Pendant with Deep Canopy PH6DC2W¹ - 2 ft White Stem Pendant with Deep Canopy PH6DC2B¹ - 2 ft Black Stem Pendant with Deep Canopy Cord CP6SW² - White Cord Pendant with Shallow Canopy CP6SB² - Black Cord Pendant with Shallow Canopy CP6DW² - White Cord Pendant with Deep Canopy CP6DB² - Black Cord Pendant with Deep Canopy Surface SM6SW - White Surface Mount with Shallow Canopy SM6SB - Black Surface Mount with Shallow Canopy SM6DW - White Surface Mount with Deep Canopy SM6DB - Black Surface Mount with Deep Canopy		Notes 1. 1ft and 2ft stems are linkable up to 12 ft. Consult factory for made to order lengths. 2. 5 ft is the standard cord length. Consult factory for made to order lengths.	



RCYA6

6" LED CYLINDER

PERFORMANCE CHART


Optics		18°	24°	36°	50°
20W	Delivered Lumens	1614	1874	1877	2161
30W	Delivered Lumens	2268	2661	2665	3094
40W	Delivered Lumens	2660	3228	3234	3815

* Values are listed at 3000K, 90+ CRI with a white bevel & trim.

COLOR TEMPERATURE MULTIPLIER FOR DELIVERED LUMENS

2700K	3000K	3500K	4000K	5000K
0.95	1.00	1.04	1.07	1.09


BEAM SPREAD



RCYA6

6" LED CYLINDER


RCYA6 DIMENSIONS



STEM PENDANT



**PH6SC1W, PH6SC1B,
PH6SC2W, PH6SC2B**

Stem Pendant with
Shallow Canopy



**PH6DC1W, PH6DC1B,
PH6DC2W, PH6DC2B**

Stem Pendant with
Deep Canopy




RCYA6

6" LED CYLINDER

CORD PENDANT


CP6SW, CP6SB

Cord Pendant with
Shallow Canopy



CP6DW, CP6DB


Cord Pendant with
Deep Canopy



SURFACE MOUNT


SM6SW, SM6SB

Surface Mount with
Shallow Canopy



SM6DW, SM6DB

Surface Mount with
Deep Canopy



RCYA6

6" LED CYLINDER

DEEP CANOPY FOR SURFACE, CORD, OR PENDANT MOUNT

