



# T616LED-G

LED GRID ROUND WALL PACK

## JOB INFORMATION

Type: \_\_\_\_\_

Catalog No: \_\_\_\_\_

Project Name: \_\_\_\_\_

Comments: \_\_\_\_\_

Prepared by: \_\_\_\_\_

T616LED-G

### FEATURES

#### USE OF PRODUCT

The intended use of this product is for decorative wall mount, building accents, pedestrian walkways, public access areas, or to accent landscape areas.

#### HOUSING

Die Cast gasketed aluminum housing with integral heat sinking and driver compartment. Nickel-Plated Stainless Steel Hardware.

#### FINISH

Matt-finished, architectural bronze powdercoat over a precise chromate conversion coating. Available in standard dark polyester bronze or consult factory for made to order architectural finishes.

#### OPTICS

Polycarbonate Opal Lens is sealed by a one-piece silicon gasket which prohibits entrance of outside contamination. Type IV distribution.

#### LED

High output LEDs offer a minimum estimated operating life of 50,000 hours in 3000K, 4000K, or 5000K (standard) with CRI>80.

#### DRIVER

Durable and long lasting LED driver operates at 120-277V and boasts a 90% power factor at 50 to 60 Hz with 0-10V Dimming Constant Current. Driver protections includes: Output open load, over-current and short-circuit, and over-temperature with auto recovery. -40°C Min Temp. 50°C Max Temp.

#### MOUNTING

Surface mount.

#### LISTINGS/COMPLIANCE

- CEC Compliant emergency driver
- CSA -Suitable for wet location.
- ANSI/UL 1598
- 8750 IP65 Sealed LED compartment.



### ORDERING INFO

SERIES	WATTAGE	COLOR TEMPERATURE	VOLTAGE	FINISH	OPTIONS
T616LED-G	12W - 12W	30K - 3000K	UNV - 120V-277V	BZ <sup>1</sup> - Bronze	PC - Photocell 120-277V
	17W - 17W	40K - 4000K		MTO <sup>2</sup> - Made to order	S2 - Microwave Sensor w/Dimming
	25W - 25W	50K - 5000K		MGTO <sup>2</sup> - Marine grade made to order	SP10 - Surge protection 10KV
					EM - Emergency battery
					CEM - Cold pack emergency battery (Integral)

#### Notes

1. Standard finish.
2. RAL number required.

# T616LED-G

LED GRID ROUND WALL PACK

## DIMENSIONS

