

Wattage & Color Temperature SELECTABLE

T621LEDB

LED MINI WALL PACK

JOB INFORMATION

Type: _____

Catalog No: _____

Project Name: _____

Comments: _____

_____

Prepared by: _____

T621LEDB

USE OF PRODUCT

The intended use of this product is for any outdoor commercial or industrial building accent, hallways, stairwells, or corridor applications. Ideal for areas requiring security or accent lighting with an optional photocell for maximum energy efficiency.

HOUSING

Rugged die cast aluminum back plate with polycarbonate front cover and lens. Housing has one coin plug on the side and back of fixture.

FINISH

Fixture is available in standard bronze finish. Consult factory for made to order finishes or for marine grade applications.

OPTICS

Durable UV-resistant polycarbonate lens. Lens is sealed by a one-piece silicon gasket which prohibits entrance of outside contaminants.

LED

EHigh output LEDs offer a minimum estimated operating life of 50,000 hours, Color temperature selectable at 3000K, 4000K and 5000K with CRI>80. Color temperature may be modified in the field. LEDs placed on high performance aluminum heatsink for reduced junction temperatures and extended life.

DRIVER

Durable and long lasting LED driver operates at 120-277V and boasts a 90% power factor at 50 to 60Hz. 0-10V dimmable driver. Working temperature -30°C to +50°C. Fixture is wattage selectable (15W, 20W, 30W). Wattage may be modified in the field.

MOUNTING

Cast-in mounting template allows direct installation over a 4" recessed outlet box or 1/2" surface conduit for easy and secure setup.

LISTINGS/COMPLIANCE

- ETL
- IP65

PERFORMANCE DATA

Wattage	Delivered Lumens		CRI
15W	1950lm	Voltage	80
20W	2600lm	120-277V	80
30W	3900lm	120-277V	80

130 lm per watt

* Values are listed at 3000K

IP Rating: IP65

ORDERING INFO

SERIES	WATT/LUMENS	COLOR TEMPERATURE	VOLTAGE	FINISH
T621LEDB	**WS30** - Wattage Selectable (15W, 20W, 30W)	**CTS** - Color Temperature Selectable (3000K, 4000K, 5000K)	**UNV** - 120V-277V	**BZ** - Bronze
	S15W - Wattage set at 15W	**S30K** - Color Temp. set at 3000K		**MTO** - Made to order
	S20W - Wattage set at 20W	**S40K** - Color Temp. set at 4000K		**MGTO** - Marine grade Made to Order
	S30W - Wattage set at 30W	**S50K** - Color Temp. set at 5000K		

INCLUDED	OPTIONS
PC - Photocell 120-277V	**EM5W** - Emergency Battery (5W)
	TRS - Tamper Resistant Screw

T621LEDB

LED MINI WALL PACK

DIMENSIONS

