



Wattage & Color Temperature
SELECTABLE

T864LEDB-FL

SQUARE FLAT TOP BOLLARD FROSTED

JOB INFORMATION

Type: _____
Catalog No: _____
Project Name: _____
Comments: _____
Prepared by: _____

T864LEDB-FL

USE OF PRODUCT

The intended use of this product is for pathways, parking lots, plazas, entrance ways, parks, and as landscape accents.

HOUSING

Extruded aluminum housing with flush mounting base.

FINISH

Weather resistant, matte-finished powder coat process for advanced protection in severe environments over a precise chromate conversion coating. Available in standard dark polyester bronze finish for impact, corrosion, and UV resistance. Consult factory for made to order architectural finishes.

OPTICS

LED engine allows for color temperature selectability. Available in 3000K, 4000K, or 5000K. Color temperature may be modified in the field or preset by factory. LED mounted to aluminum heat sink for maximum life output and thermal management. LED color rendering index is 70+ CRI.

DRIVER

Durable and long lasting LED driver operates at 120-277V and boasts a 90% power factor at 50 to 60 Hz with 0-10V Dimming Constant Current. Fixture is wattage selectable (14W, 19W, 24W). Watts may be modified in the field or preset by factory. -40°C Min Temp to 50°C Max Temp.

CONTROLS

Fixture may be controlled by photocell.

MOUNTING

- Mounting kit with anchor bolts are included.
- Bollard must be mounted on a concrete base. (Supplied by others)

LISTINGS/COMPLIANCE

- UL - Listed for wet location (IP65)



WATTAGE/LUMEN CHART

Wattage	Delivered Lumens	CCT Selectable	CRI
14W	1800lm	3000K, 4000K, 5000K	>70
19W	2470lm	3000K, 4000K, 5000K	>70
24W	3100lm	3000K, 4000K, 5000K	>70

ORDERING INFO

SERIES	WATTAGE	COLOR TEMPERATURE	VOLTAGE	FINISH	OPTIONS
T864LEDB-FL	WS24 - Wattage Selectable (14W, 19W, 24W) S14W - Set at 14W S19W - Set at 19W S24W - Set at 24W	CTS - Color Temperature Selectable (3000K, 4000K, 5000K) S30K - Set at 3000K S40K - Set at 4000K S50K - Set at 5000K	UNV - 120V-277V	BZ ¹ - Bronze MTO ² - Made to Order MGTO ² - Marine Grade Made To Order	PC - Photocell 120-277V EM4W - Emergency Battery 4W CEM15W - Cold Pack Emergency Battery HSS - 180° Shield SDT - 347/480 Stepdown Transformer TRS - Tamper Resistant Screw BRBK - Bollard Retrofit Base Kit MTOH - Made to Order Height


Notes

1. Standard finish.
2. RAL number required.

T864LEDB-FL

SQUARE FLAT TOP BOLLARD FROSTED

BOLLARD DIMENSIONS



SQUARE ANCHOR PLATE DIMENSIONS

