




JOB INFORMATION	TYPE:
	CATALOG NO.
	PROJECT NAME:
	COMMENTS:
PREPARED BY:	

T325LED

ARCHITECTURAL LED AREA LUMINAIRE

DIMENSION



FEATURES

USE OF PRODUCT

The intended use of this product is for recreational areas, streets, pedestrian areas, and any open commercial or industrial space.

HOUSING

Luminaire constructed of a weathertight unit fabricated from aluminum .063\"

FINISH

Matt-finished, thermoset polyester oven baked powdercoat. Available in standard dark polyester bronze finish or consult factory for made to order architectural finishes

OPTICS

- Clear tempered glass lens for impact resistance.
- One-piece, di-formed, heavy gauge aluminum frame and lens are sealed by gasket against moisture, bugs, and dust lens frame opens on two-piece take-apart hinges.
- Segmented or hydroform reflector, depending on ANSI type specified. All reflectors have a highly reflective specular aluminum finish.

LED

High output LEDs offer a minimum estimated operating life of 50,000 hours in 3000K, 3500K, 4000K, or 5000K (standard) with CRI>83. LEDs placed on high performance aluminum heatsink for reduced junction temperatures and extended life.

DRIVER

Durable and long lasting LED driver operates at 120-277V and boasts a 90% power factor at 50 to 60 Hz with 0-10V Dimming Constant Current. Driver protections includes: Output open load, over-current and short-circuit, and over-temperature with auto recovery. Step down transformer may be utilized for 480V or 347V applications.

LISTINGS/COMPLIANCE

- CSA -Suitable for wet locations.
- Dark Sky Compliant

ACCESSORIES

Dusk to dawn with twist lock photo control for easy maintenance.



SIZE A: LENGTH: 22.00\"

ORDERING INFORMATION

T325LED							
---------	--	--	--	--	--	--	--

SERIES	SIZE	WATT/LUMENS	VOLTAGE	COLOR TEMP	MOUNTING	FINISH	OPTIONS
T-SERIES LED	A - 22\"	1,2 10 - 10W/1050	UNI12 -120V-277V	30 - 3000K	SBL - Swivel Bracket / Trunnion Mount	4 BZ - Bronze	PC1 - Photocell 120V
	B - 33\"	1,2 18 - 18W/1890	347 - 347V	35 - 3500K	SFL - Slipfitter	5 MTO - Made to Order	PC2 - Photocell 277V
		1,2 30 - 30W/3150	480 - 480V	40 - 4000K	YM - Large Yoke Mount		PN - Photocell NEMA
		1,2 45 - 45W/4725		3 50 - 5000K	AM6S - 6\"		VG - Visor Guard/Glare Shield
		1,2 57 - 57W/5985			AM10S - 10\"		MS - Motion Sensor
		1,2 85 - 85W/8925			AM6R - 6\"		WC - Wireless Control
		1,2 110 - 110W/11550			AM10R - 10\"		WSF - Wired Single Fuse
		2 170 - 170W/17850			TPMA - Adjustable Direct Pole Mount Arm		SDT - Step Down Transformer
		2 225 - 225W/23625			WMB90SF - Wall Mount 90° Bracket		EM - Emergency Battery Pack
					WMSF - Wall Mount Plate for Slipfitter		
					WMAM - Wall Mount Plate for Arm Mount		

- 1 Available in size A
- 2 Available in size B
- 3 Standard color temperature
- 4 Standard color finish
- 5 RAL number required